

MATERIAL SAFETY DATA SHEET

IDENTITY (As used on label and list)

TURBO SET I (ACCELERATOR)

Part Numbers for this MSDS:

40-120, 40-130, 40-140, 40-150

SECTION I

Manufacturer's Name

Palm Labs., Inc

Address (Number, Street< City, State and ZIP Code

10 Office Way

Hilton Head, SC 28829

U.S.A.

Emergency Telephone Number

800- 964 6660

Telephone Number For Information.

(800)-964-8581

Date Prepared

9/6/2011

Signature of Preparer (optional)

SECTION II - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s)	OSHA PEL	ACGIH TLV	Other Limits Recommended
Synthetic Hydrocarbon	300	no list	HMIS

H-1, F-2, R-0

TSCA- Registry Number Proprietary

DOT- Petroleum Distillate N.O.S. UN1268 III

CERCLA- No special reporting if spilled, contact local authorities.

SARA- Title III Hazard Class, Fire

SECTION III - Physical/Chemical Characteristics

Boiling Point

320-351° F.

Specific Gravity (H₂O=1)

.75

Vapor Pressure(mm/Hg.)

2 mmHg./100° F.

Melting Point

less than 32° F.

Solubility in Water

Less than .01% @ 77° F.

Evaporation Rate

(Butyl Acetate = 1) .3 Approximate

Appearance and Odor

Clear colorless liquid with light naphtha odor.

Section IV - Fire And Explosion Hazard Data

Flash Point (Method Used)

104° F. (TCC)

Flammable Limits

@77° F.

LEL

1.2

UEL

9.6

Extinguishing Media

Foam or dry chemical, water mist to cool.

Special Fire Fighting Procedures

Water spray to cool surfaces and protect personnel. Foam or dry chemical to extinguish. Avoid spraying water into storage

Container.

Unusual Fire and Explosion Hazards

Can release vapors that form combustible mixtures at or above flashpoint.

Section V - Reactivity Data

Stability	Unstable		Conditions To Avoid None
	Stable	X	
Incompatible Materials to Avoid	None		
Hazardous Decomposition Or Byproducts None			
Hazardous Polymerization	May Occur		Conditions to Avoid None
	Will Not Occur	X	

Section VI - Health Hazard Data

Routes of Entry	Inhalation? yes	Skin? low toxicity	Ingestion minimal toxicity
Health Hazards (<i>Acute And Chronic</i>) Inhalation- High vapor concentrations are irritating to eyes and respiratory tract. May cause headache and dizziness. Ingestion- Get medical help. Do not induce vomiting.			
Carcinogenicity None	NTP	IARC Monographs?	OSHA Regulated? Combustible
Signs and Symptoms of Exposure. See Above			
Medical Conditions Generally Aggravated by Exposure Respiratory if very high concentration.			
Emergency and First Aid Procedure Eyes- Flush with water until irritation subsides, if irritation continues get medical help. Wash skin with soap/water. Remove clothes, wash before reuse.			

Section VII - Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled
Eliminate sources of ignition. Small spills, allow to dry or cleanup with absorbent material. This material will be combustible.

Waste Disposal Method.
Consult an expert on waste disposal to ensure conformity to local regulations.

Precautions to be Taken in Handling and Storing
None for safety. Product will last longer if stored in a cool and dry environment.

Other Precautions.
Do not spray near sources of ignition, open fires, lite cigarettes etc.

Section VIII - Control Measures

Respiratory Protection (*Specify Type*)
None specific, local ventilation adequate.

Ventilation	Local Exhaust Recommended	Special None
	Mechanical (<i>General</i>)	Other
Protective Gloves Yes	Eye Protection Yes	
Other Protective Clothing or Equipment		

Work/Hygienic Practices
Standard solvent -use work practices as if with Naphtha